

IBANEZ FACTORY SPECS

SCALE	25- ¹ / ₂ " (648 mm)	
RADIUS	17" (430 mm) at both the fretboard and bridge	
FRETS	.115" x .055" (2.9 mm x 1.4 mm)	
STRINGS	D'Addario nickel wound, .009" – .042"	
RELIEF	Adjusted perfectly straight and played clean	
NUT	Bass side (low E)	Treble side (high e)
	.016" (0.4 mm)	.006" (0.15 mm)
ACTION		
	At 17 th fret	3/64"+004"(1.2 mm) 1/32" (0.88 mm)
POLEPIECE HEIGHT		
	Neck pickup:	1/16" (1.6 mm) 5/64" (2.0 mm)
	Middle pickup:	1/8" (3.17 mm) 5/64" (2.0 mm)
	Bridge pickup:	1/32" (0.8 mm) 5/64" (2.0 mm)

IBANEZ TOVÁRNÍ SPECIFIKACE

MENZURA	25- ¹ / ₂ " (648 mm)	
RADIUS	17" (430 mm) hmatník i kobyłka	
PRAŽCE	.115" x .055" (2.9 mm x 1.4 mm)	
STRUNY	D'Addario nickel wound, .009" – .042"	
RELIÉF KRKU	Nastaven úplně do roviny a hratelně čistě (bez drnčení strun)	
	Basová strana (nízké E)	Výšková strana (vysoké e)
NULTÝ PRAŽEC	.016" (0.4 mm)	.006" (0.15 mm)
VÝŠKA STRUN		
	na 17. pražci	3/64"+004"(1.2 mm) 1/32" (0.88 mm)
VÝŠKA SNÍMAČŮ (pólových nástavců)		
	Krkový snímač:	1/16" (1.6 mm) 5/64" (2.0 mm)
	Střední snímač:	1/8" (3.17 mm) 5/64" (2.0 mm)
	Kobyłkový snímač:	1/32" (0.8 mm) 5/64" (2.0 mm)